

PANEL

POOL FAMILY 1 PH/REDOX


Data Sheet

DESCRIPTION


- ✓ Peristaltic pumps with built in REDOX and PH controllers
- ✓ TAL system (protection system from overdosing)
- ✓ Suitable for oxidant and acid chemicals dosage.
- ✓ Proportional dosage according to Set Point
- ✓ Buffer solutions PH 7.00 – 9.00 e REDOX 468 mV
- ✓ SCHUKO plug
- ✓ PH and REDOX probes with Epoxy body, 1 meter cable

OPTIONAL


- ✓ Electrical authorization to dosage via a second power supply cable connected to the circulation system
- ✓ Possible Graphic customizations
- ✓ Level probe predisposition (alternative to TAL system)
- ✓ ON / OFF switch on the pumps




PH CONTROL INSTRUMENT

	Range	0..14 pH
	Pressure	3 BAR
	T°C	70°C
	Body	Epoxy
	Sensor	Platinum
	Conn.	BNC
	Diameter	Ø 12mm

PRO-PH



CHLORINE CONTROL INSTRUMENT VIA REDOX

	Range	±1500mV / offset ±20 mV
	Pressure	3 BAR
	T°C	70°C
	Body	Epoxy
	Sensor	Platinum
	Conn.	BNC
	Diameter	Ø 12mm

PRO-REDOX

PANEL POOL FAMILY 1 PH-REDOX

Data
Sheet

DESCRIPTION		
	Standard Material	Upon Request
Standard Version		
Pump body	PP	-----
Roller	DELRIN	-----
Tube	Santoprene	-----
Power Supply	230 V 50 – 60 Hz	-----
Consumption	35 Watt	-----
Net weight	1,0 kg.	-----
Ring Nuts	PP 1/8"	-----
Fittings	PP 4 x 6 mm	-----
Probe connections	BNC	-----

TECHNICAL SPECIFICATION										
Standard	Max l/h	Pressure		Max cc / min	Tube Santoprene	Pump body	Watt	RPM	Weight	
		Bar	PSI						kg.	Lbs
1,8-01	1,8	01	14,7	0,14	4 x 7	PP	35	15	1,0	2,4
2,4-01	2,4	01	14,7	0,18	4 x 7	PP	35	20	1,0	2,4

